



**FOR PROFESSIONALS WHO WANT THE JOB DONE RIGHT**

## ACRYLIC BONDING AGENT MEETS ASTM C 1042



**1 GALLON PAIL**

**Item 348075**

### Key Features

- Improves flexural strength, bond strength & impact resistance of mortars & concrete.
- Concrete & mortar fortified with RD BOND resistance to cycles of freezing & thawing & to penetration of chloride ions.
- Minimizes cracks in concrete, stucco & plaster

## PVA BONDING AGENT MEETS ASTM C 1059



**1 GALLON PAIL**

**Item 436200**

### Key Features

- Re-emulsifiable/rewettable; VOC compliant
- Excellent bonding agent/superior adhesive strength
- Admixture drastically increases durability, adhesion & curing of cement base mortars & stucco
- Can be used when there is a delay between primer application & subsequent topping or underlayment

## MULTIPURPOSE GROUT ASTM C1107, & CRD C621 USDA ACCEPTED



50 LB BAG

Item 383050

### Key Features

- Designed for a wide range of consistencies
- Grouting anchor bolts, baseplates & equipment
- Flowable / Pumpable for easy placement
- NonMetallic /Non corrosive
- Extendable with pea stone (deep applications)
- One-component - Just add water

## COMING SOON!

## RAPID SET REPAIR MORTAR, HIGH EARLY STRENGTH, IN HORIZONTAL APPLICATIONS ASTM C928, & AASHTO T260



50 LB BAG

Item 388030

### Key Features

- One-component, drypolymer, Just add water.
- Easytouse, flowable consistency
- Air entrained for excellent freeze/thaw durability
- Horizontal & formed vertical applications
- High early strength & resumption of traffic

## COMING SOON!

## POLYMER MODIFIED CONCRETE RESURFACER



40 LB BAG

Item 384070

### Key Features

- Contains no crystalline silica for ultrafine repairs.
- Offers superior durability for all interior & exterior applications
- Resurfacing concrete horizontal, vertical, & overhead surfaces.
- Can be used as a skim patch or trowel down underlayment
- Horizontal repairs subjected to Light traffic p to 1/4"

## COMING SOON!

## POLYMER MODIFIED TWO COMPONENT CONCRETE REPAIR MORTAR WITH CORROSION INHIBITOR



50 LB BAG

Item 384060

### Key Features

- Two component versatility of polymer
- Contains integral corrosion inhibitor
- Suitable for vertical/overhead repairs from feathered edge to 2"
- Interior/Exterior overlayment applications
- Excellent durability & adhesion
- Excellent freeze-thaw durability

**COMING SOON!**

**POLYMER MODIFIED  
RAPID SETTING MULTI-  
PURPOSE CONCRETE  
REPAIR MORTAR FOR  
VERTICAL/OVERHEAD &  
HORIZONTAL APPLICATIONS**

**40 LB BAG**

**Item 384080**



### Key Features

- Can be featheredged & shaped by shaving
- Lifts up to 1" in thickness (up to 2" in small areas)
- Interior & exterior repairs
- Excellent durability & adhesion
- Dries to the color of concrete
- One-component - Just add water

**FAST SETTING HYDRAULIC  
CEMENTOCK POURABLE  
NONSHRINK MORTAR  
STOPS FLOWING WATER**

**50 LBS & 10 LBS**

**50# Item 348050  
10# Item 348054**



### Key Features

- Single component; just add water & use
- Sets hard in 35 minutes; stops flowing water
- Expands as it sets, bonds strongly to concrete & makes a watertight repair
- Controlled expansion as it sets
- Nonmetallic; will not shrink or oxidize
- Certified to NSF/ANSI Standard 61 for potable water contact

**QUICKSETTING NONSHRINK  
ANCHORING CEMENT  
(EXPANDS AS IT  
SETS HARD IN 12-15 Min.)**

**50 LBS & 10 LBS**

**50# Item 389100  
10# Item 389101**



### Key Features

- Sets hard in 1215 minutes; speeds production
- High strength up to 2000 psi. in 1 hour at 72 °F.
- Controlled expansion as it sets
- Nonmetallic; maintains volume stability over time
- Waterproof, resistant to freeze/thaw
- Provides durable, longlasting anchoring application

**CURE & SEAL  
30 S/B ACRYLIC CURE &  
SEAL MEETS ASTM C309  
MEETS ASTM C1315**

**5 GALLON PAIL**

**Item 670350**



### Key Features

- Useful for decorative concrete & cure & seal applications.
- Dried Coating is USDA accepted.
- Meets VOC emission requirements for curing & sealing compounds (EPA limit < 700 g/L)
- Non-yellowing, medium to high gloss finish.

## CURE & SEAL WB - WATER BASED



**5 GALLON PAIL**

Item **670200**  
Model **670200**

### Key Features

- Provides a tough glossy film that is resistant to abrasion & common staining materials
- Prevents the adhesion of cementitious droppings & the penetration of most oils & greases
- Reduces maintenance & clean-up costs
- Cleans & brightens floors

## CURE & SEAL 25-25% SOLIDS SOLVENT-BASED



**5 GALLON PAIL**

Item **670300**  
Model **670300**

### Key Features

- Meets ASTM C1315 Class A and ASTM C309, Type 1, Classes A&B.
- Meets VOC emission requirements for curing and sealing compounds (EPA limit < 700 g/L). USDA accepted

## RELEASE - GENERAL PURPOSE REACTIVE FORM RELEASE AGENTS (MULTIPLE SIZES AVAILABLE)



**5 GALLON PAIL**

Item **348080**  
Model **348080**

**55 GALLON DRUM**

Item **348090**  
Model **348090**

### Key Features

- Improves release of formwork
- Reduces concrete buildup on formwork & liners
- Reduces cleaning of formwork
- Protects formwork against rust
- Leaves no residue, stain or discoloration

## SHOP OUR PREMIUM RED DIAMOND PRODUCTS AT

[www.DarraghCompany.com](http://www.DarraghCompany.com)



**Darragh**